

Fosroc Life Jacket

(Formerly Galvashield LJ)

Galvanic corrosion protection system for severe exposure concrete elements

Uses

Fosroc Life Jacket is designed to reinstate and actively protect reinforced concrete/structural steel elements subject to the most severe exposure conditions. Typical applications include columns and piles subject to wet-dry tidal cycling in marine environments.

Advantages

- No post installation maintenance required
- Self powered and self regulating
- 'All in one' repair and protection system
- Longest life expectancy of any galvanic system
- Satisfies the 100mV criteria for effective cathodic protection
- Proven technology with measured performance
- Provides highly cost effective repair vs comparable systems
- Quick, easy and low cost installation, no costly electrical work or monthly monitoring
- Fully compatible with selected Renderoc repair mortars

Description


Fosroc Life Jacket is a galvanic protection system based upon the installation of prefabricated heavy duty marine quality GRP jackets incorporating a zinc anode system conforming to ASTM A-190. The anode system is connected to the steel reinforcement to provide the required protective current to the steel.

Fosroc Life Jacket can be supplied in rectangular, circular or flat formats to suit substrate profile.

Fosroc Life Jacket assembly is supplied with a minimum of 8 non-conductive "stand-offs" per face which are used to secure the anode in place whilst simultaneously achieving the optimum position of the jacket in relation to the structure it is protecting.

Following the fixing of Fosroc Life Jacket, repairs and jacket fill are accomplished by pouring into place Renderoc LJ a conductively compatible repair material.

A replacable bulk anode can be incorporated into the system in order to provide considerable lifetime extension where required.



Design Criteria

Fosroc Life Jacket is a 'cathodic' protection system utilising the long proven principle of galvanic protection to provide long term durability to both new and existing structures in conditions of extreme exposure such as splash and tidal zones in marine environments.

Fosroc Life Jacket satisfies the 100mV potential shift requirement for effective cathodic protection as specified under NACE (National Association of Corrosion engineers) Standard RP 0290-90.

In line with other 'cathodic' protection systems, Fosroc Life Jacket must be designed and the installation supervised by a specialist in the field of corrosion control.



Fosroc Life Jacket

Standards Compliance

Fosroc Life Jacket will, when installed and connected in accordance with approved instructions, exceed the minimum 15 year life criteria laid down by FHWA and DOT specifications. The design of Fosroc Life Jacket follows comprehensive criteria established for the patented 'Lifejacket'™ system developed by the Alltrista Corporation. (In certain circumstances life expectancy may be increased by the addition of bulk anodes).

Specification

The galvanic protection jacket shall be Fosroc Life Jacket, a composite GRP jacket incorporating a zinc anode system.

Renderoc LJ a conductively compatible repair material will be used to fill the void between the jacket and the concrete/ steel substrate. This material shall be supplied by the same supplier as Fosroc Life Jacket to guarantee compatibility of product.

Instructions for use

Preparation

Saw cut the extremities of the repair area to a minimum depth of 10mm thus feather edging is avoided and a square edge is created. Deteriorated concrete shall be broken out from around and behind steel reinforcing in accordance with good concrete practice.

All exposed steel reinforcement must be cleaned to a bright condition paying particular attention to the back of exposed steel bars. Abrasive blasting is recommended for this process.

In order for Fosroc Life Jacket to function correctly, steel reinforcing must be continuous, if not, continuity must be established throughout the structure prior to making

connections.

Connection can be made through a single excavation to a sound reinforcing bar in the area requiring protection. This will become the negative connection and must be made in compliance with FHWA and DOT specification requirements.

A standard junction box is used to house all functional wire connections and may serve as a site for shutting the circuit when measuring current and voltage outputs.

The Fosroc Life Jacket system is a two piece 'Tongue and Groove' interlocking jacket assembly. It is positioned and held in place with non conductive fasteners and sealed moisture tight with an approved adhesive.

Temporary formwork is installed to the lower annulus to retain the structural high strength repair which is poured into the jacket cavity, this formwork is later removed to allow saltwater migration to wet the anode interface within the jacket.

When the final wire connection is made the system becomes immediately operational providing a non-interrupted protective current to the corroded structure.

Estimating

Supply

Each Fosroc Life Jacket assembly is supplied prefabricated ready to use, in accordance with prior dimensions received from the project.

Precautions

Health and safety

There are no known health and safety hazards associated with Fosroc Life Jacket.

For health and safety requirements on Renderoc LJ refer to the product data sheet.



Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Service. **All Fosroc datasheets are updated on a regular basis. It is the user's responsibility to obtain the latest version.**

Head Office

telephone: (+9714) 2039699

fax: (+9714) 2859649

email: agf@fosroc.com

Regional offices

Abu Dhabi, Al Gurg Fosroc
Bahrain, YBA Kanoo
Kuwait, Boodai
Oman, Al Amana
Qatar, Tadmur

telephone: 673 1779
telephone: 17738200
telephone: 4817618
telephone: 24815080
telephone: 4432365

fax: 673 1449
fax: 17732828
fax: 4832124
fax: 24817554
fax: 4419517

email: abudhabi@fosroc.com
email: bahrain@fosroc.com
email: kuwait@fosroc.com
email: oman@fosroc.com
email: qatar@fosroc.com

Al Gurg Fosroc LLC

Post Box 657, Dubai
United Arab Emirates

www.fosroc.com

