



Nitoseal Debonding Tape

Polyethylene coated Kraft Paper with a high tack pressure sensitive adhesive

Uses

Nitoseal Debonding Tape is designed to isolate the sealant from the bitumen containing filler board wherever polyethylene backing rod is not used.

It is placed beneath the sealant at the base of the joint to ensure three side adhesion is prevented.

Advantages

Prevents three side adhesion of joint sealants.

Properties

Backing:	Polyethylene Coated Kraft Paper
Total Thickness:	0.153 mm – 0.160 mm
Temperature Range of adhesive:	40°C Max
Shelf life:	1 year from date of manufacture

Instruction for use

Joint surfaces must be clean, dry and free from all dirt, laitance, old sealant and foreign substances.

Place the Nitoseal Debonding Tape at the base of the joint, If primer is needed, apply primer only on the sides carefully avoiding the tape surface.

Apply the sealant according to its own method statement and technical data sheet instructions.

Health and Safety

Nitoseal Debonding Tape is non-hazardous.



Al Gurg Fosroc LLC

Post Box 657, Dubai
United Arab Emirates

www.fosroc.com

Important Note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard terms and conditions of sale, copies of which may be obtained on request. Whilst Fosroc endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Telephone:
(+9714) 2858606

fax:
(+9714) 2859649

email:
agf@fosroc.com

Registered Office: 215 Community, Street No. 13, Nad Al Hamar Road, Al Ramool Industrial Estate, Rashidiya, Dubai

UAE/0778/13/A