



Fosroc Dekguard Filler

Acrylic, intercoat pin hole filler

Uses

Levelling and filling of intercoat pin holes and minor irregularities prior to the application of pigmented Dekguard topcoats.

Advantages

- Single component no mixing required.
- Easy to apply.
- Can be applied to vertical surfaces without slumping.

Description

Dekguard Filler, an external quality filler is based on acrylic resin and fine fillers.

It has been specially developed for use with the Dekguard concrete protection system.

Technical support

Fosroc offers a comprehensive technical support service to specifiers, end users and contractors. It is also able to offer on-site technical assistance, an AutoCAD facility and dedicated specification assistance in locations all over the world.

Properties

Form	:	Single component white paste
Bulk density	:	1500 kg/m ³
Application temperature	:	5 to 40°C
Overcoating time	:	12 hours minimum

Instructions for use

Coating

If Dekguard Primer* or Nitoprime DG* is to be used it must be applied prior to applying Dekguard Filler. Dekguard Filler should be tightly trowelled onto the prepared surface ensuring that all pin holes and defects are completely filled to produce a smooth even finish. It is essential that the material is well worked into the surface in order to ensure maximum adhesion and minimum thickness. Dekguard Filler can be applied to existing coatings. The surface of the existing coating has to be cleaned and abraded. In order to determine if Dekguard Filler is compatible with the existing coating it may be necessary to carry out adhesion tests.

Excellent adhesion of the topcoat will be achieved provided that the Dekguard Filler surface is not contaminated. Where contamination does occur, e.g. from general dust or cement debris, then this should be removed prior to overcoating.

Cleaning

Tools and equipment should be cleaned with water immediately after use.

Estimating

Pack Size

Dekguard Filler	:	18 litre pack
------------------------	---	---------------

Coverage

Coverage of Dekguard Filler is wholly dependent upon surface conditions, site trials are therefore recommended to ascertain actual usage on uneven substrates.

Storage

Shelf life

Dekguard Filler	:	6 months
------------------------	---	----------

Store Dekguard Filler upright in unopened original containers in cool dry conditions. Storage outside these guidelines will impair shelf life.

Fosroc Dekguard Filler

Precautions

Health and safety

Wear suitable protective clothing, gloves and eye protection. The use of barrier creams provide additional skin protection. In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention immediately. If swallowed seek medical attention immediately - **do not** induce vomiting.

Fire

Dekguard Filler is non-flammable

Additional Information

Fosroc manufactures a wide range of complementary products which include :

- waterproofing membranes & waterstops
- joint sealants & filler boards
- cementitious & epoxy grouts
- specialised flooring materials

Fosroc additionally offers a comprehensive package of products specifically designed for the repair and refurbishment of damaged concrete. Fosroc's 'Systematic Approach' to concrete repair features the following :

- hand-placed repair mortars
- spray grade repair mortars
- fluid micro-concretes
- chemically resistant epoxy mortars
- anti-carbonation/anti-chloride protective coatings
- chemical and abrasion resistant coatings

For further information on any of the above, please consult your local Fosroc office - as below.

* Denotes the trademark of Fosroc International Limited

† See separate data sheet



Al Gurg Fosroc LLC

Post Box 657, Dubai
United Arab Emirates

www.fosroc.com

Important note

Fosroc products are guaranteed against defective materials and manufacture and are sold subject to its standard Conditions for the Supply of Goods and Service. **All Fosroc datasheets are updated on a regular basis. It is the user's responsibility to obtain the latest version.**

Head Office

telephone: (+9714) 2039699

fax: (+9714) 2859649

email: agf@fosroc.com

Regional offices

Abu Dhabi, Al Gurg Fosroc
Bahrain, YBA Kanoo
Kuwait, Boodai
Oman, Al Amana
Qatar, Tadmur

telephone: 673 1779
telephone: 17738200
telephone: 4817618
telephone: 24815080
telephone: 4432365

fax: 673 1449
fax: 17732828
fax: 4832124
fax: 24817554
fax: 4419517

email: abudhabi@fosroc.com
email: bahrain@fosroc.com
email: kuwait@fosroc.com
email: oman@fosroc.com
email: qatar@fosroc.com

